



Compatto a cassetta



Modello N.	Unità interna			AUXG09KVL A	AUXG12KVL A	AUXG14KVL A
Classe kW	kW			2,5	3,5	4,0
Alimentazione				Monofase, ~ 230 V, 50 Hz		
Pressione sonora	Raffreddamento	H/M/L/O	dB(A)	33/31/29/27	37/34/31/28	38/35/32/29
	Riscaldamento			34/32/29/27	37/34/31/29	43/38/34/30
Potenza sonora	Raffreddamento	H	dB(A)	46	49	50
	Riscaldamento			47	49	55
Portata d'aria	Raffreddamento	H/M/L/O	m³/h	540/490/440/390	610/530/470/410	680/580/490/410
	Riscaldamento			540/490/440/390	610/530/470/410	790/680/580/450
Dimensioni nette	mm			245x570x570	245x570x570	245x570x570
Peso	kg (lbs)			15 (33)	15 (33)	15 (33)
Pannello				UTG-UFGF-W	UTG-UFGF-W	UTG-UFGF-W
Diametro del tubo di collegamento	Liquido/Gas	mm		6,35/9,52	6,35/9,52	6,35/9,52

Canalizzabile Slim



Modello N.	Unità interna			ARXG09KLLAP	ARXG12KLLAP	ARXG14KLLAP
Classe kW	kW			2,5	3,5	4,0
Alimentazione				Monofase, ~ 230 V, 50 Hz		
Pressione sonora	Raffreddamento	H/M/L/O	dB(A)	28/27/26/25	29/28/27/26	32/30/28/26
	Riscaldamento			28/26/25/24	29/28/27/24	32/30/28/25
Potenza sonora	Raffreddamento	H	dB(A)	57	58	60
	Riscaldamento			57	58	60
Portata d'aria	Raffreddamento	H/M/L/O	m³/h	600/550/500/450	650/600/550/480	800/700/600/480
	Riscaldamento			600/550/500/450	650/600/550/480	800/700/600/480
Dimensioni nette	mm			198x700x620	198x700x620	198x700x620
Peso	kg (lbs)			17 (37)	17 (37)	17 (37)
Diametro del tubo di collegamento	Liquido/Gas	mm		6,35/9,52	6,35/9,52	6,35/9,52
Pressione statica esterna	Pa			da 0 a 90	da 0 a 90	da 0 a 90
Pompa di scarico				Standard		